

2008

**Virginia Department of Transportation
Daily Traffic Volume Estimates
Including Vehicle Classification Estimates**

where available

Special Locality Report

117

City of Lexington

Information in this report is included in Report

81

(Rockbridge County)

Prepared By

**Virginia Department of Transportation
Traffic Engineering Division**

In Cooperation With

**U.S. Department of Transportation
Federal Highway Administration**

Virginia Department of Transportation
Traffic Engineering Division
Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled “Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes” includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled “Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99”.

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a “Combined Traffic Estimates for Parallel Roadways on this Route” or “Combined Traffic” identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate “NA” for not available.

VDOT’s traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating “NA” for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate “NA” for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems



Interstate Route

Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.



US Route



Virginia State Route



Frontage Road (F precedes frontage route number)



Secondary Route

Special Routes



Bus - Business Route

Bypas - Bypass Route

Truck - Truck Route



ALT - Alternate Route

Wve - Wve Route connector



P - Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.



The VDOT Maintenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation
Traffic Engineering Division
2008
Annual Average Daily Traffic Volume Estimates By Section of Route
City of Lexington

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus	Truck				QC	K Factor	QK	Dir Factor	AAWDT	QW
							2Axle	3+Axle	1Trail	2Trail						
11 S Lee Highway	From: SCL Lexington City of Lexington	0.59	9200	F	98%	1%	1%	0%	1%	0%	C	0.094	F	10000	F	
11 N Lee Highway	To: Main St City of Lexington	0.04	10000	G	98%	1%	1%	0%	1%	0%	F	0.086	F	0.530	11000	G
11 N Lee Highway	To: Bus US 11 City of Lexington	0.08	21000	G	98%	0%	1%	0%	0%	0%	C	0.083	N	0.562	22000	G
Bus 11 Main St	To: NCL Lexington City of Lexington	0.39	3100	G	98%	1%	1%	1%	0%	0%	C	0.097	F	0.506	3400	G
Bus 11 Main St	To: Thornhill Rd City of Lexington	0.16	5200	G	98%	1%	1%	1%	0%	0%	F	0.091	F	0.672	5600	G
Bus 11 Main St	To: Wallace St City of Lexington	0.31	4600	F	99%	0%	0%	0%	0%	0%	C	0.095	F		5000	F
Bus 11 Main St	To: White St City of Lexington	0.31	3500	G	99%	0%	1%	0%	0%	0%	F	0.103	F		3800	G
	Combined Traffic Estimates for 2 Parallel Roadways on this Route:		5800	G	96%	1%	3%	0%	0%	0%	F	0.085	F	0.560	6200	G
Bus 11 Main St	To: Nelson St City of Lexington	0.24	5500	F	96%	1%	1%	2%	0%	0%	C	0.091	F		5900	F
	Combined Traffic Estimates for 2 Parallel Roadways on this Route:		9300	F	95%	1%	3%	1%	0%	0%	C	0.09	F		10000	F
Bus 11 Main St	To: Jefferson St City of Lexington	0.37	9700	G	99%	0%	1%	0%	0%	0%	F	0.091	F	0.535	11000	G
Bus 11 Main St	To: Letcher St City of Lexington	0.34	9000	F	99%	0%	1%	0%	0%	0%	C	0.093	F	0.607	9800	F
Bus 11 Jefferson St	To: US 11 N Lee Highway; S Lee Highway City of Lexington	0.35	2200	G	92%	2%	5%	0%	0%	0%	F	0.102	F		2400	G
	Combined Traffic Estimates for 2 Parallel Roadways on this Route:		5800	G	96%	1%	3%	0%	0%	0%	F	0.085	F	0.560	6200	G
Bus 11 Jefferson St	To: US 60 Nelson St City of Lexington	0.24	3800	F	92%	2%	5%	0%	0%	0%	C	0.097	F		4200	F
	Combined Traffic Estimates for 2 Parallel Roadways on this Route:		9300	F	95%	1%	3%	1%	0%	0%	C	0.09	F		10000	F
60 Nelson St	To: Bus US 11 Main St City of Lexington	0.25	4100	G	98%	0%	1%	0%	0%	0%	C	0.102	F	0.638	4400	G
60 Nelson St	To: WCL Lexington City of Lexington	0.33	5100	F	98%	0%	1%	0%	0%	0%	C	0.095	F		5500	F
	To: Woods Creek City of Lexington															
	To: Glasgow Street															

Virginia Department of Transportation
Traffic Engineering Division
2008
Annual Average Daily Traffic Volume Estimates By Section of Route
City of Lexington

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW	
							2Axle	3+Axle	1Trail	2Trail							
60 Nelson St	From: Glasgow Street		0.14	5500	G	98%	0%	1%	0%	0%	0%	F	0.092	F	0.619	6000	G
	To: Lee Street																
60 Nelson St	From: Lee Street		0.17	7700	G	98%	1%	1%	0%	0%	0%	F	0.085	F	0.583	8400	G
	To: Randolph Street																
60 Nelson St	From: Randolph Street		0.21	6800	F	98%	0%	1%	0%	0%	0%	C	0.096	F	0.595	7400	F
	To: Spotswood Dr																
60 Nelson St	From: Spotswood Dr		0.35	16000	F	98%	1%	1%	0%	0%	0%	C	0.098	F	0.567	17000	F
	To: ECL Lexington at US 11																
251 Thornhill Rd	From: WCL Lexington		0.38	4400	F	97%	1%	1%	0%	1%	0%	C	0.101	F	4800	F	
	To: Link Rd																
251 Link Rd	From: Link Rd		0.24	3900	G	97%	1%	1%	0%	1%	0%	F	0.087	F	0.572	4300	G
	To: Main St																

Virginia Department of Transportation
 Traffic Engineering Division
 2008
 Annual Average Daily Traffic Volume Estimates By Section of Route
 City of Lexington

Route	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
						2Axle	3+Axle	1Trail	2Trail							
City of Lexington																
① Diamond St	0.36	1100	F	97%	1%	1%	1%	1%	0%	C	0.168	F	0.691	1200	F	2008
② Lee St	0.08	1800	G	97%	1%	1%	0%	0%	0%	C	0.095	F	0.573	2000	G	2008
④251 Thornhill Rd	0.38	1900	F	100%	0%	0%	0%	0%	0%	C	0.098	F	0.879	2100	F	2008
④252 Enfield Rd	0.43	1400	F	98%	1%	1%	0%	0%	0%	C	0.096	F	0.578	1500	F	2008
④252 Lime Kiln Rd	0.32	2000	F	98%	1%	1%	0%	0%	0%	C	0.095	F	0.56	2100	F	2008
④254 Ross Rd	0.31	1100	F	99%	1%	0%	0%	0%	0%	C	0.105	F	0.565	1200	F	2008
④254 Jackson Ave	0.27	1600	F	99%	0%	1%	0%	0%	0%	C	0.113	F	0.684	1700	F	2008
④255 Houston St	0.40	1900	F	99%	0%	1%	0%	0%	0%	C	0.1	F	0.565	2100	F	2008
④255 Houston St	0.15	2200	G	99%	0%	1%	0%	0%	0%	F	0.103	F	0.515	2400	G	2008
④256 McDowell St	0.05	490	G	97%	1%	1%	0%	0%	0%	C	0.136	F	0.587	530	G	2008
④257 Walker St	0.40	2300	F	97%	1%	1%	0%	0%	0%	C	0.095	F	0.53	2500	F	2008
④258 Preston St	0.05	2100	G	97%	1%	1%	0%	0%	0%	F	0.111	F	0.894	2200	G	2008
④260 Henry St	0.05	980	G	97%	1%	2%	1%	0%	0%	C	0.1	F	0.53	1100	G	2008
④261 Lewis St	0.08	3400	G	98%	0%	1%	0%	0%	0%	C	0.108	F	0.509	3600	G	2008
④261 Washington St	0.30	3000	F	97%	0%	1%	1%	1%	0%	C	0.101	F	0.622	3300	F	2008
④261 Washington St	0.06	3700	G	98%	0%	1%	0%	0%	0%	F	0.104	F	0.673	4000	G	2008
④261 Washington St	0.06	4800	G	98%	0%	1%	0%	0%	0%	F	0.093	F	0.555	5200	G	2008
④261 Washington St	0.21	3200	F	98%	0%	1%	0%	0%	0%	C	0.092	F		3500	F	2008
④262 Borden Rd	0.34	1000	F	98%	0%	1%	0%	0%	0%	C	0.092	F	0.541	1100	F	2008
④263 Lewis St	0.33	1300	G	99%	0%	1%	0%	0%	0%	C	0.149	F	0.589	1400	G	2008

Virginia Department of Transportation
 Traffic Engineering Division
 2008
 Annual Average Daily Traffic Volume Estimates By Section of Route
 City of Lexington

Route	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
						2Axle	3+Axle	1Trail	2Trail							
City of Lexington																
④266 Spottswood Dr	0.40	2300	F	99%	0%	From: Houston St				C	0.107	F	0.539	2500	F	2008
						To: Nelson St										
④267 White St	0.18	1400	G	99%	0%	From: Jefferson St				F	0.105	F	0.653	1500	G	2008
						To: McLaughlin St										
④267 McLaughlin St	0.28	2300	F	98%	0%	From: White St				C	0.104	F	0.566	2500	F	2008
						To: Glasgow St										
④267 Glasgow St	0.06	1100	G	99%	0%	From: McLaughlin St				C	0.113	F	0.729	1200	G	2008
						To: Nelson St										
Campbell Lane		1200	F	98%	0%	From: McCorkle Drive				C	0.126	F	0.507	1200	F	2008
						To: US 11										
Edmondson Ave		400	G			From: Jackson Ave					0.149	F	0.575	400	G	2008
						To: Main St										
Taylor St		1400	G			From: Wallace St					0.136	F	0.612	1600	G	2008
						To: Houston St										
Tucker St		280	G			From: Washington St					0.089	F		310	G	2008
						To: Massie St										
Waddell St		1300	F	93%	3%	From: US 11 Main St				C	0.173	F	0.682	1300	F	2008
						To: Wallace St										
White St		3200	F	99%	0%	From: Jefferson St				C	0.108	F		3200	F	2008
						To: Main St										