2014

Virginia Department of Transportation Daily Traffic Volume Estimates Including Vehicle Classification Estimates

where available

Special Locality Report 233

Town of Haymarket

Information in this report is included in Report

76

(Prince William County)

Prepared By

Virginia Department of Transportation Traffic Engineering Division

In Cooperation With

U.S. Department of Transportation Federal Highway Administration

Virginia Department of Transportation Traffic Engineering Division Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1 Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:


- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems

North 81	Interstate Route	Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.
29	US Route	



(600) Secondary Route

Virginia State Route

Special Routes

Bus - Business Route Bypas - Bypass Route Truck - Truck Route ALT - Alternate Route Wye - Wye Route connector		
	Bypas - Bypass Route Truck - Truck Route ALT - Alternate Route	Bypas - Bypass Route Truck - Truck Route ALT - Alternate Route

- P Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.
- The VDOT Maintainenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation Traffic Engineering Division 2014

Annual Average Daily Traffic Volume Estimates By Section of Route Town of Haymarket

Route	Jurisdictio	n	Length	AADT	QA	4Tire	Bus		Tru 3+Axle			QC	K Factor	QK	Dir Factor	AAWDT	QW
	From:		W	CL Haymarl	cet												
15 James Madison Hwy	Town of Haymarket	(Maint: 76)	0.10	32000	N	96%	1%	1%	1%	2%	0%	Ν	0.074	Ν	0.567	33000	Ν
/ James Madison Llung	Town of House of House	(Maint, 76)	0.21	I-66 31000		95%	1%	1%	1%	2%	0%	F	NA			22000	
[15] James Madison Hwy	Town of Haymarket	(Mairit. 76)		L Haymark	G	95%	170	1%	170	270	0%	Г	IVA			32000	G
15 Ramp	Town of Haymarket	(Maint: 76)	US 15 Ja 0.17	ames Madis 14000									0.108	_		14000	G
[15] Ramp	Town of Haymarket	(Mairit. 76)	0.17	I-66 East	G								0.108	Г		14000	G
	Fron:																
55 Washington St	Town of Haymarket	(Maint: 76)	0.43	CL Haymarl 13000	cet G	99%	0%	0%	0%	0%	0%	_	0.089	_	0.559	12000	G
55 Washington St	Town of Haymarket	(IVIAITIL. 70)				33 /6	0 /0	0 /0	0 /6	0 /0	0 /6	'	0.009	'	0.556	13000	G
	To: From:	(14.1		Old Caroli													
$\binom{55}{}$ Washington St	Town of Haymarket	(Maint: 76)	0.41	9400	G	99%	0%	0%	0%	0%	0%	С	0.079	F	0.543	9700	G
	10.			CL Haymark											QK AAWDT QW Factor		
East (66)	From:	(14.1		CL Haymarl								_					_
(66)	Town of Haymarket		0.84	30000	Α	92%	1%	1%	0%	7%	0%	F	0.113	Α			
	Combined Traffic Estimates for 2 Parallel	Roadways on th		59000	Α	92%	1%	1%	0%	6%	0%	F	NA			60000	Α
	10.			CL Haymark													
West (66)	From:	(14.1		CL Haymarl								_					_
(66)	Town of Haymarket		0.04	20000	Α	92%	1%	1%	0%	6%	0%	F	0.134	Α			
	Combined Traffic Estimates for 2 Parallel	Roadways on th	s Route:	39000	Α	92%	1%	1%	0%	6%	0%	F	NA			38000	Α
West	To: From:			US 15													
(66)	Town of Haymarket	(Maint: 76)	0.80	29000	Α	92%	1%	1%	0%	6%	0%	F	0.118	Α		29000	Α
(88)	Combined Traffic Estimates for 2 Parallel	'			A	92%	1%	1%	0%	6%	0%	F	NA				Α
	To:			L Haymark			.,,	Ť	0,0	• , •	0,0	•				00000	
West	From:	I_6/	6-W TO RT	-		ORTH		Ė									
Ramp	Town of Haymarket		0.15	NA	111001	OKIII							NA			NA	
00)	To:	,	15 US 15-		1 & TO	RT 66											

4/21/2015 7

Virginia Department of Transportation Traffic Engineering Division 2014 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Haymarket

						TOWITO	і пауша	inct								
Route	Length	AADT	QA	4Tire	Bus		Tru 3+Axle	_		QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
Town of Havmarket		From														
F293)	0.03	NA				D	ead End				NA			NA		
F293)	0.00	To				WCL	Haymarke	et								
		From				SCL	Haymarke	t								
625 Old Carolina Rd	0.08	6500	N	97%	1%	2%	1%	0%	0%	N	NA			6500	N	2014
Old Carolina Rd	0.24	5800 From	R				01 Fayette				NA			NA		12/07/200
625 Old Carolina Rd	0.35	5500 From	R				Vashingto				NA			NA		11/04/201
		From	1				Haymarke									
1103) Greenhill Crossing Lar	ne 0.42	520	R			76-1106	Saint Pau	l Dr			 NA			NA		12/16/200
Greenhill Crossing Lar	10 0.12	To	<u> </u>			SR 55 Joh	n Marshal	l Hwy			— T			101		12/10/200
		From					ıl-de-Sac									
Jockey Club Lane	0.38	130	R								NA			NA		02/01/201
76)		To				76-1106	Saint Pau	l Dr								
Jockey Club Lane	0.05	60 From	R								NA			NA		07/12/20
76		To				Cυ	ıl-de-Sac									
		From				Cu	ıl-de-Sac									
1105 Little John Court	0.07	60	R								NA			NA		05/13/201
<u> </u>		То			76-	1103 Gree		sing Lane								
Saint Paul Dr	0.07	From	ᄂᢩ			Cu	ıl-de-Sac							NIA		00/01/00
	0.27	460	R			SR 55 Joh	n Marchal	Hwy			NA		NA			02/01/201
		From	SR 55 John Marshall Hwy 76-625 Old Carolina Rd								_					
Tayette St	0.26	730	G	96%	1%	2%	0%	0%	0%	С	NA			730	G	2014
		To									—					
1301) Fayette St	0.05	1000 From	R			/0-130.	2 Payne La	me			NA			NA		01/04/201
Fayette St		To				CD 55 Inh	n Manahal	I I Ivv			_					
1301) Fayette St	0.13	450 From	R			SR 55 Joh	n warshar	пшу			NA			NA		08/14/201
Tagette St		То				D	ead End									
		From				76-130	1 Fayette	St								
1302 Payne Lane	0.07	150	R								NA			NA		01/04/201
76)		To				76-625 C	ld Carolin	a Rd								
		From				76-625 C	ld Carolin	a Rd								
1303 Jordan Lane	0.28	40	R								NA			NA		01/04/201
<u> </u>		То				D	ead End									
Madison Ct	0.01	From	ᄂ			D	ead End							NIA		01/04/001
1304 Madison St	0.21	230	R								NA —			NA		01/04/201
Livetina Dath Mari	0.10	From	ᆫ			SR 55 Joh	n Marshal	l Hwy						NIA		04/05/004
1304 Hunting Path Way	0.13	480 To	R			D	ead End				NA			NA		01/05/201
		From						111			_					
1305) Bleight Dr	0.20	320	R			SR 55 Joh	n Marshai	Hwy			NA			NA		01/04/201
1305 Bleight Dr	0.20	To	r:			D	ead End				— T			101		01/01/201
		From				76-1304 I		th Rd			i					
Madison Court	0.06	45	R								NA			NA		05/14/201
(6)		To				Cu	ıl-de-Sac									
		From				76-130	5 Bleight	Dr								
3311 Dogwood Park Place	0.10	350	R			-	-				NA			NA		12/16/200
<u> </u>		То	<u> </u>			76-3314 S					<u> </u>					
O W 1 . 15 . 15		From			76	6-3311 Do	gwood Par	k Place								00/0:/25
(3312) Walnut Park Dr	0.07	80 To	R			76 2214 0		ouls D			NA			NA		03/24/200
		10	1			76-3314 S	ycamore P	ark Dr								

4/21/2015 8

Virginia Department of Transportation Traffic Engineering Division 2014 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Haymarket

Route	Length	AADT	QA	4Tire	Bus	Truck 2Axle 3+Axle 1Trail 2T	(.)(;	K Factor	QK	Dir Factor	AAWDT	QW	Year
Town of Havmarket													
		From			,	76-3314 Sycamore Park Dr							
(3313) Cypress Park Lane	0.04	30	R					NA			NA		12/16/200
<u> </u>		To	1			76-3312 Walnut Park Dr							
		From				Dead End							
(3314) Sycamore Park Dr	0.15	60	R					NA			NA		08/19/201
76		To				Dead End							
		From	1			76-3592 Caboose Tl							
3591 Coach Way	0.05	400	R					NA			NA		09/09/201
76		To				SR 55 Washington St							
		From				Cul-de-Sac							
(3592) Caboose TI	0.16	190	R					NA			NA		09/09/201
(3592) Caboose II		To				76-3593 Track Ct							
		From				Cul-de-Sac							
(3593) Track Ct	0.13	45	R			Cui-de-Bac		NA			NA		08/15/2013
(3593) Track Ct	00												00/10/201
	0.00	From	<u> </u>			76-3592 Caboose Tl					114		00/00/004
(3593) Track Ct	0.08	150	R					NA			NA		09/09/201
		To	<u> </u>			Cul-de-Sac							
<u> </u>	•	From				76-3592 Caboose Tl				•		•	
Southern Crossing St 3594	0.10	48	R					NA			NA		09/09/2013
76)		To				76-3593 Track Ct							

4/21/2015 9