2014

Virginia Department of Transportation Daily Traffic Volume Estimates Including Vehicle Classification Estimates

where available

Special Locality Report 306

Town of Strasburg

Information in this report is included in Report

85

(Shenandoah County)

Prepared By

Virginia Department of Transportation Traffic Engineering Division

In Cooperation With

U.S. Department of Transportation Federal Highway Administration

Virginia Department of Transportation Traffic Engineering Division Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1 Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:


- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems

North 81	Interstate Route	Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.
29	US Route	



(600)	Secondary Route
(OUU)	Secondary house

Virginia State Route

Special Routes

Bus - Business Route Bypas - Bypass Route Truck - Truck Route ALT - Alternate Route Wye - Wye Route connector		
	Bypas - Bypass Route Truck - Truck Route ALT - Alternate Route	Bypas - Bypass Route Truck - Truck Route ALT - Alternate Route

- P Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.
- The VDOT Maintainenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation Traffic Engineering Division 2014

Annual Average Daily Traffic Volume Estimates By Section of Route Town of Strasburg

Pouto	Jurisdiction	Longth	AADT	ΟΛ	4Tiro	Puo		Tru	ck		QC	K	QK	Dir	AAWDT	OW/
Route	Jurisdiction	Length	AADT	QA	4Tire	Bus	2Axle	3+Axle	1Trail	2Trail	QU	Factor	QK	Factor	AAWDI	QW
	From:	S	CL Strasbur	g												
11 Stover Ave	Town of Strasburg (Maint: 85)	0.38	6600	F	98%	0%	1%	0%	1%	0%	С	0.113	F	0.732	6900	F
\bigcirc	To:		King St													
~~~	From:		Stover Ave													
11 King St	Town of Strasburg (Maint: 85)	0.24	7500	G	97%	1%	1%	0%	0%	0%	С	0.113	Ν	0.732	7500	G
$\hookrightarrow$	To:		Holliday St													
√11 King St	Town of Strasburg (Maint: 85)	0.16	7100	F	98%	0%	1%	0%	1%	0%	F	0.109	F	0.695	7400	F
(11)	То:		5 Massanutt	ten St			i i									
	From:		R 55 King S													
(11) (55) N Massanutten St	Town of Strasburg (Maint: 85)	0.23	13000	F	98%	0%	0%	0%	1%	0%	F	0.087	F	0.594	13000	F
~ ~	To: From:	SR 55 N	John Mars	hall Hw	y											
N Massanutten St	Town of Strasburg (Maint: 85)	0.70	13000	F	98%	0%	0%	0%	1%	0%	С	0.094	F	0.588	13000	F
$\bigcirc$	To:	N	CL Strasbu	rg												
	From:	W	CL Strasbu	rg												
55 John Marshall Hwy	Town of Strasburg (Maint: 85)	0.64	3400	F	97%	1%	1%	1%	1%	0%	С	0.091	F	0.506	3600	F
,	To:	US 11 W. Massanutten St														
	From:	US 1	1 Massanutt	ten St												
(55) (11) N Massanutten St	Town of Strasburg (Maint: 85)	0.23	13000	F	98%	0%	0%	0%	1%	0%	F	0.087	F	0.594	13000	F
	To:	US 11 Massanutten St														
	From:	US 11	E, Massanu	itten St												
( ₅₅ ) King St	Town of Strasburg (Maint: 85)	0.60	6800	F	96%	1%	1%	1%	2%	0%	С	0.095	F	0.545	7100	F
$\smile$	To		Eberly St													
55 Front Royal Rd	Town of Strasburg (Maint: 85)	0.58	3800	F	96%	1%	1%	1%	2%	0%	F	0.098	F	0.556	4000	F
3,44	To:		CL Strasbur	rg												

4/21/2015 7

# Virginia Department of Transportation Traffic Engineering Division 2014 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Strasburg

						10001101	Strasbt	arg								
Route	Length	AADT	QA	4Tire	Bus		Tru 3+Axle			QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
Town of Strasburg		From	1			Fran	nklin St									
1210 Third St	0.07	0	R			1141	ikiiii ot				NA			NA		08/25/201
85)		Te				Ki	ing St									
1 Branch St	0.26	400		98%	0%	Ca	pon St 0%	0%	0%	С	0.126	F	0.544	420	F	2014
1 Branch St	0.20	<b>400</b>		30 /6	0 /6		nklin St	0 78	0 76		0.120	ļ	0.544	420	ļ	2014
Outstand Ot	0.40	From		000/	00/		Franklin S		00/	_	2400	_	0.500	000	_	004.4
2 Orchard St	0.18	<b>260</b>	F	98%	0%	1% US 11 5	0% Stover Ave	0% e	0%	F	0.122	F	0.562	280	F	2014
		Fron	1		SR	2 55 Front R										
3 Eberly St	0.10	350	F	98%	0%	1%	0%	0%	0%	F	0.113	F	0.656	370	F	2014
<u> </u>		From			85-635	Bowman H		CL Strasb	urg							
4 Aileen Ave	0.28	280	' <u>Е</u>	98%	0%	Qu 1%	een St 0%	0%	0%	F	0.174	F	0.809	290	F	2014
•		To	c				ad End									
O 01 01	0.00	Fron		222/	00/		ing St	00/	22/	_		_	0.750	500	_	2011
5 Sharpe St	0.08	550	F	98%	0%	1% Ou	0% ieen St	0%	0%	F	0.19	F	0.753	580	F	2014
		Fron					ME US 11									
6 Hite Ln	0.30	120	F								0.206	F	0.518	120	F	2014
<u> </u>		Tz Fron				US 11 Old	d Valley P	ike			_					
6 Radio Station Rd	0.54	1600 _{To}	F			D	- 1 F 1				0.114	F	0.6	1600	F	2014
		From	1				hard St									
(1966) Franklin St	0.18	320	F	97%	2%	0%	1%	0%	0%	С	0.109	F	0.539	340	F	2014
		Tr				Bra	anch St									
Ash Ct	0.77	Fron		000/	10/	85-638 W			00/	_	0.005	_	0.550	000	_	0014
(1967) Ash St	0.77	940	F	98%	1%	1%	0%	0%	0%	С	0.095	F	0.552	990	F	2014
(1967) Washington St	0.37	2600 From	†	98%	1%	306-197 1%	71 Capon S 0%	0%	0%	F	0.093	F	0.655	2700	F	2014
(1967) 11 dogto et	0.07		·		. , ,	US 11 N N				•	<u> </u>	•	0.000		•	
(1967) Washington St	0.43	1700 From	F	99%	0%	0%	0%	0%	0%	С	0.11	F	0.556	1800	F	2014
$\bigcirc$		T _e Fron				Virg	ginia St									
(1967) Washington St	0.18	730	F	99%	0%	0%	0%	0%	0%	F	0.103	F	0.562	770	F	2014
		From				Eberly St; I		burg								
(1971) Capon St	0.16	2500		99%	0%	1%	ing St 0%	0%	0%	F	0.116	F	0.757	2600	F	2014
(1071)		To					anch St									
(1971) Capon St	0.50	1900	F	99%	0%	1%	0%	0%	0%	С	0.126	F	0.762	2000	F	2014
		To			1	SR 55 John	Marshall	Hwy								
(1974) Holliday St	0.30	2300		94%	4%		CL Strasbi		00/	С	0.248	F	0.559	2400	F	2014
(1974) Holliday St	0.30	2300		94%	4 70	1%	0%	1%	0%	-	0.246	Г	0.558	2400	Г	2014
(1974) Holliday St	0.07	3900 From	F	94%	4%	1%	igh St 0%	1%	0%	F	0.239	F	0.594	4100	F	2014
1974) ************************************		т	_				ieen St	.,.				-				
(1974) Holliday St	0.08	2800 From	F	94%	4%	1%	0%	1%	0%	F	0.177	F	0.529	3000	F	2014
		To From				US 11	1 King St									
(1974) Holliday St	0.08	1600	F	94%	4%	1%	0%	1%	0%	F	0.123	F	0.668	1700	F	2014
		To	1				ington St									
(1975) Queen St	0.19	470		97%	2%	Sha 1%	arpe St 0%	0%	0%	F	0.167	F	0.749	500	F	2014
1973)	30	Te	-				liday St	- / 0	- 70	-	<u> </u>	•				
(1975) Queen St	1.10	2300 From	F	97%	2%	1%	0%	0%	0%	С	0.161	F	0.596	2500	F	2014
$\bigcirc$		To	:				ont Royal	Rd								

4/21/2015 8

# Virginia Department of Transportation Traffic Engineering Division 2014 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Strasburg

Longth	AADT	ΟΛ	4Tiro	Bus	Truck				00	K	OK	Dir	A A \A/D.T	OW	Year
Lengin	AADI	QA	4 i ire		2Axle	3+Axle	1Trail	2Trail	QC	Factor	QN	Factor	AAWDI	QW	rear
	From:				H	ligh St									
	180	F								0.15	F	0.571	180	F	2014
						ueen St									
	From:		East Queen Street												
	2900	G	97%	1%	1%	0%	0%	0%	С	NA			2900	G	2014
	To:				SR 55	King Stree	et			$\Box$					
	From:				1	US 11									
	730	G	99%	0%	0%	0%	0%	0%	С	NA			730	G	2014
	To:		Lee Street												
	Length	180 To T	180 F To  From  2900 G To:  From	180 F To  From  2900 G 97% To  From	180 F  To  From:  2900 G 97% 1%  To  From:	Length   AADT   QA   4Tire   Bus   2Axle	Canon   Cano	Continue	Continue	Carry   Carr	AADT   QA   4Tire   Bus   2Axle 3+Axle 1Trail 2Trail   QC   Factor	Company   Comp	AADT   QA   4Tire   Bus   2Axle 3+Axle 1Trail 2Trail   QC   Factor   QK   Factor   Factor	AADT	AADT   QA   4Tire   Bus   2Axle 3+Axle 1Trail 2Trail   QC   Factor   QK   Factor   AAWDT   QW

4/21/2015 9