2016

Virginia Department of Transportation Daily Traffic Volume Estimates Including Vehicle Classification Estimates

where available

Special Locality Report 208

Town of Dillwyn

Information in this report is included in Report

14

(Buckingham County)

Prepared By

Virginia Department of Transportation Traffic Engineering Division

In Cooperation With

U.S. Department of Transportation Federal Highway Administration

Virginia Department of Transportation Traffic Engineering Division Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- **F** Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- **F** Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems

North 81	Interstate Route	Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.									
29	US Route										
7	Virginia State Rou	te									
(F241)	Frontage Road (F	precedes frontage route number)									
600	Secondarv Route										
		Special Routes									
Bus 29 ALT 220	Bus - Business Ro Bypas - Bypass R Truck - Truck Rou ALT - Alternate Ro Wye - Wye Route	oute te oute									
		Southbound or Westbound direction lanes of a numbered route a different road facility than the other direction.									
600		inenance Jurisdiction number is displayed below the Secondary Rout									

The VDOT Maintainenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation Traffic Engineering Division 2016 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Dillwyn

Route	Jurisdiction	Length A	ADT QA	4Tire	Bus		Tru 3+Axle	-	2Trail	QC	K Factor	QK Dir Factor	AAWDT	QW
	From:	WCL Dillwyn; 14	4-1010 Goldr	nine St										
15 Oak St	Town of Dillwyn (Maint: 14)	0.58 8	500 N	91%	1%	1%	1%	6%	0%	Ν	0.087	0.53	8800	Ν
~	Tor	14-1003	E, Main St											
15 Main St	Town of Dillwyn (Maint: 14)	0.52 8	500 N	91%	1%	1%	1%	6%	0%	Ν	0.087	0.53	8800	Ν
\smile	To:	ECL Dillv	wyn; 14-650											

Virginia Department of Transportation Traffic Engineering Division 2016 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Dillwyn

Route	Length	ΔΔΩΤ	QA	4Tire	Bus		of Dillwy Tru			QC	K	QK	Dir	AAWDT	OW	Year
	Length		QA	4110	Dus	2Axle	3+Axle	1Trail	2Trail	QU	Factor	GI	Factor	AAWDT	QW	i eai
Town of Dillwvn		From				SCL	Dillwyn									
629 Rosney Rd	0.41	380	G	94%	1%	2%	2%	1%	0%	С	0.129		0.638	390	G	2016
		From	1				5 Main St									
Hancock St	0.07	190	R			SCL	Dillwyn				NA			NA		03/29/2012
14		To				0.07 N	IN of SCL	,								
Hancock St	0.14	260	R								NA			NA		03/29/2012
		To From					Camden			_						
(1001) Hancock St	0.10	120	G	96%	2%	1%	1%	0%	0%	F	0.182		0.5	120	G	2016
(1001) Hancock St	0.26	Ton From	G	96%	2%	14-1008 \ 1%	Warehouse 1%	e St 0%	0%	С	0.127		0.546	180	G	2016
(1001) Hancock St	0.20	170		30 /8	2 /0				0 /8	U	0.127		0.540	100	u	2010
(1001) Hancock St	0.08	From 290	G	96%	2%	14-1005	Culberth 1%	0%	0%	F	0.155		0.659	300	G	2016
(1001) Hancock St		То				US 1:	5 Main St									
		From	L			14-1001	Hancock	St								
(1002) Camden St	0.17	200 To	R			14.100)3 Main St				NA			NA		04/07/2015
		From	1				Dillwyn									
(1003) Main St	0.24	790	G	95%	1%	1%	1%	3%	0%	F	0.099		0.543	820	G	2016
14		To				14-1002	Camden	St								
(1003) Main St	0.09	590	G	95%	1%	1%	1%	3%	0%	F	0.104		0.553	610	G	2016
		To From					Warehouse	e St								
(1003) Main St	0.30	500 To	G	95%	1%	1%	1%	3%	0%	F	0.122		0.527	520	G	2016
		From				US 15 E, N	Hancock									
(1004) Carie St	0.07	R			14-1001	HallCOCK	31			NA			NA		04/07/2015	
14		170 ⊤₀	-			14-100	7 Conner S	St								
	0.07	From	Ļ			De	ad End									04/07/0045
(1005) Culberth St	0.07	30	R								NA			NA		04/07/2015
(1005) Culberth St	0.07	From 30	R			14-100	7 Conner S	St			NA			NA		04/07/2015
(1005) Culberth St	0.07	То				14-1001	Hancock	St						IN/A		04/07/2013
		From	-			De	ad End									
(1006) White St	0.07	30	R								NA			NA		04/07/2015
		To	-			14-100	7 Conner S	St								
(1006) White St	0.07	60	R								NA			NA		04/07/2015
(1006) White St	0.10	From				14-1001	Hancock	St			NA			NA		04/07/2015
(1006) White St	0.10	60 To	R			14-100	3 Main St	t						INA.		04/07/2013
		From	1				6 White S									
(1007) Conner St	0.06	90	R								NA			NA		04/07/2015
		To				14-1005	Culberth	St								
(1007) Conner St	0.07	130	R								NA			NA		04/07/2015
	0.05	To From				14-100	4 Carie S	t						NIA		04/07/0015
(1007) Conner St	0.05	380 то	R			T	IS 15				NA			NA		04/07/2015
		From	1				Hancock	St								
(1008) Warehouse St	0.13	110	R								NA			NA		04/07/2015
1111111111111		To					3 Main St	1								
(1009) LeSueur St	0.38	From	R			SCL	Dillwyn							NA		04/07/2015
(1009) LeSueur St	0.30	140 ^{To}				14-100	3 Main St	t			NA			INA		04/07/2015

Virginia Department of Transportation Traffic Engineering Division 2016 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Dillwyn

Route	Length	AADT	QA	4Tire	Bus	Truck 2Axle 3+Axle 1Trai	QC	K Factor	QK Dir Facto	AAWDT O	N Year
Fown of Dillwyn		From				14 1014 NOL D'II					
(1010) Gold Mine St	0.19	250	R			14-1014, NCL Dillwyn		NA		NA	04/09/2015
(1010) Gold Mine St	0.10	To				US 15 E, Oak St					01/00/2010
		From	1			Dead End					
1011 14 Mitchell St	0.07	30	R					NA		NA	04/07/201
14		To				14-1012 Carter St		_			
Mitchell St	0.05	190	R					NA		NA	04/07/201
14		To				US 15 Main St					
_		From				Dead End					
1012 14 Carter St	0.04	50	R					NA		NA	03/29/2012
14		To				14-1011 Mitchell St					
Carter St	0.06	140	R					NA		NA	03/29/2012
14		To				14-629 Rosney Rd					
~		From				Dead End					
1013 Hardiman Rd	Rd 0.10	6	R					NA		NA	03/27/2012
		To				14-629 Rosney Rd					
		From				Dead End					
1015 Brickyard Dr	kyard Dr 0.07	2	R					NA		NA	03/29/2012
-		To				0.07 MN Dead End					
1015 Brickyard Dr	0.05	8	R					NA		NA	03/29/2012
<u> </u>		To: From:				14-1018 Brickyard Dr					
1015 Brickyard Dr	0.10	340	R					NA		NA	04/09/2015
		To				US 15 Oak St					
\sim		From				Dead End			NA		
1016 Whetstone Lane	Lane 0.06	50	R					NA		NA	03/29/2012
\checkmark		To	<u> </u>			14-1002 Camden St					
	0.00	From	لي			Dead End				N14	04/00/0047
1018 Brickyard Dr	0.08	300 To:	R			14 1015 Printroad Dr		NA		NA	04/09/2015
		10.				14-1015 Brickyard Dr					