2016

Virginia Department of Transportation Daily Traffic Volume Estimates Including Vehicle Classification Estimates

where available

Special Locality Report

316

Town of Urbanna

Information in this report is included in Report



(Middlesex County)

Prepared By

Virginia Department of Transportation Traffic Engineering Division

In Cooperation With

U.S. Department of Transportation Federal Highway Administration

Virginia Department of Transportation Traffic Engineering Division Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- **F** Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- **F** Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems

North 81	Interstate Route	Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.										
29	US Route											
7	Virginia State Route											
(F241)	Frontage Road (F precedes frontage route number)											
600	Secondarv Route											
		Special Routes										
Bus 29 ALT 220	Bus - Business Ro Bypas - Bypass R Truck - Truck Rou ALT - Alternate Ro Wye - Wye Route	oute te oute										
		Southbound or Westbound direction lanes of a numbered route a different road facility than the other direction.										
600		inenance Jurisdiction number is displayed below the Secondary Rout										

The VDOT Maintainenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation Traffic Engineering Division 2016 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Urbanna

Route	Jurisdiction	Length AADT	QA	4Tire	Bus		Tru 3+Axle			()(:)	K Factor	QK Dir Factor	AAWDT	QW
	From:	ECL Urbann	a											
(227)	Town of Urbanna (Maint: 59)	0.63 3100	Ν	97%	0%	1%	1%	1%	0%	Ν	0.092	0.559	3200	Ν
\smile	To:	WCL Urbann	a											

Virginia Department of Transportation Traffic Engineering Division 2016 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Urbanna

							of Urbar									
Route	Length	AADT	QA	4Tire	Bus		Tri 3+Axle		2Trail	QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
Town of Urbanna		From														
Rappahannock Ave	0.33	740	G	98%	0%	2%	SR 227 0%	0%	0%	С	0.103		0.5	770	G	2016
Rappahannock Ave	0.14	440 From	G	97%	0%	3%	6 Marston 0%	0%	0%	F	0.115		0.525	450	G	2016
Rappahannock Ave	0.18	From 160	G	97%	0%	3%	07 Taylor A 0% 014 Kent S	0%	0%	С	0.117		0.546	170	G	2016
		From	1:				ead End									
Uirginia St	0.23	260	R								NA			NA		03/30/2015
		To				SR 2	27; 59-100)5								
(1003) Prince George St	0.12	From 660	R				Prince Geo	rge St			NA			NA		06/11/2015
<u> </u>		To					SR 227									
(1004) Wattling St	0.05	From 60	" R			Γ	ead End				NA			NA		03/30/2015
(1004) Wattling St	0.00	т					SR 227							1.07.1		00/00/2010
		From	1:				SR 227									
Cross St	0.25	600	G	97%	0%	2%	0%	0%	0%	С	0.109		0.559	630	G	2016
ng		Te				59-100	6 Marston	Ave								
(1005) Cross St	0.15	420	G	97%	0%	2%	0% 07 Taylor A	0%	0%	F	0.124		0.635	430	G	2016
(1005) Cross St	0.09	210 From	R				13 West A				NA			NA		06/11/2015
(1005) Cross St	0.06	90	R			39-10	15 West A	ve			NA			NA		06/11/2015
50		То				59-1008	Colorado	Ave								
		From			5	9-1001 R	appahanno	ck Ave								
1006 59 Marston Ave	0.10	220	G	98%	0%	1% 59-10	0%	0% St	0%	С	0.162		0.525	220	G	2016
Marston Ave	0.14	80	R								NA			NA		06/11/2015
23		To	0			Γ	ead End									
\bigcirc = 1 A	0.40	From 80			5	9-1001 R	appahanno	ck Ave								00/11/0015
1007 Taylor Ave	0.10		R								NA			NA		06/11/2015
	0.07	From				59-10	005 Cross	St						NIA		00/11/0015
1007 Taylor Ave	0.07	200 _{то}	R			59-1022	2 Chandler	Ave			NA			NA		06/11/2015
		From	12		5		appahanno									
Colorado Ave	0.13	70	R		5	, 100110	appunumo				NA			NA		06/11/2015
59		То	0			59-1	014 Kent S	St								
		From				59-1003	Prince Geo	rge St								
(1009) Prince George St	0.04	840 TO	R				GD 227				NA			NA		06/11/2015
			,				SR 227									
(1010) Grace Ave	0.05	From 690	R				SR 227				NA			NA		06/11/2015
(1010) Grace Ave						50.10	25 Hilliard	St								
(1010) Grace Ave	0.06	420 From	R			59-10	2 <i>3</i> minaru	51			NA			NA		06/11/2015
(1010) Grace Ave		т				59-1	019 Park S	St								
(1010) Grace Ave	0.08	250 From	R			571					NA			NA		06/11/2015
<u></u>		Τ				59-10	20 Bonner	St								
<u></u>	/	From				Γ	ead End									
Howard St	0.30	190	R			20.11	0.5 0 -	C+			NA			NA		06/11/2015
_		From			_		005 Cross									
(1013) West Ave	0.17	90	R		5	9-1001 R	appahanno	ck Ave			NA			NA		06/11/2015
(1013) West Ave	0.17	т				59-1	014 Kent S	St								50/11/2010

Virginia Department of Transportation Traffic Engineering Division 2016 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Urbanna

							UI UIDAI								
Route	Length	AADT	QA	4Tire	Bus		Tru 3+Axle		QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
Town of Urbanna															
	0.10	From	Ļ		5	9-1001 R	appahanno	ck Ave					NIA		00/11/0015
(1014) Kent St	0.19	110 To	R			59-10	13 West A	Ve		NA			NA		06/11/2015
		From	1				SR 227	ve		1					
(1015) Watling St	0.11	260	R				3K 227			NA			NA		06/11/2015
(1015) Watling St		To				ECI	L Urbanna								
		From				:	SR 227								
(1017) Upton Lane	0.04	630	R							NA			NA		06/18/2015
33		To				D	ead End								
		From				D	ead End								
(1018) Obert St	0.13	130 ^{To}	R							NA			NA		06/11/2015
			<u> </u>		5		appahanno								
(1019) Park St	0.12	From 150	R			59-10	21 Linden	St		NA			NA		06/11/2015
(1019) Park St	0.12	1 00			5	9-1001 R	appahanno	ck Ave					INA		00/11/2015
		From			5		ead End	CK IIVC		1					
(1020) Bonner St	0.05	180	R			D	eau Enu			NA			NA		05/29/2012
(1020) Bonner St		То				50.10	21 Linder	G4							
(1020) Bonner St	St 0.12		R			59-10	21 Linden	St		NA			NA		06/11/2015
(1020) Bonner St	0=	170 ^{To}	<u> </u>		5	9-1001 R	appahanno	ck Ave							
		From					019 Park S			1					
(1021) Linden St	0.14	110	R							NA			NA		06/11/2015
59		To				D	ead End								
		From				D	ead End								
(1022) Chandler Ave	0.04	30	R							NA			NA		03/30/2015
		To				59-100	7 Taylor A	Ave							
(1022) Chandler Ave	0.05	120	R							NA			NA		03/30/2015
		To				D	ead End								
		From				D	ead End								
Hilliard St	0.06	100 ^{To}	R			50 101	0.0			NA			NA		05/24/2012
		From	<u> </u>				10 Grace A								
(1026) Red Cedar Lane	0.06	30	R		5	9-1001 R	appahanno	ck Ave		NA			NA		05/24/2012
(1026) Red Cedar Lane	0.00	То				Cı	ul-de-Sac						11/1		05/24/2012
		From	•		5		appahanno	ck Ave		1					
(1027) Parkview Lane	0.06	70	R			2-1001 K	аррананно	CA I IVU		NA		NA	NA	03/:	03/30/2015
155		То				Cı	ul-de-Sac								
		From			5	9-1001 R	appahanno	ck Ave	 						
(1028) Manor Rd	0.12	130	R							NA			NA		06/11/2015
23		То				Cı	ul-de-Sac								