### 2018

# Virginia Department of Transportation Daily Traffic Volume Estimates Including Vehicle Classification Estimates

where available

### Special Locality Report 276

Town of Painter

Information in this report is included in Report

01

(Accomack County)

Prepared By

Virginia Department of Transportation Traffic Engineering Division

In Cooperation With

U.S. Department of Transportation Federal Highway Administration

#### Virginia Department of Transportation Traffic Engineering Division Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

#### **Publication Notes**

#### Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

#### Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

#### QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

**2Axle Truck**: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1 Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

#### Route Shield Legend

#### Route Systems

North 81	Interstate Route	Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.
29	US Route	
7	Virginia State Rou	ute

Frontage Road (F precedes frontage route number)

(600) Secondary Route

#### Special Routes

Bus	Bus - Business Route
29	Bypas - Bypass Route
	Truck - Truck Route
ALT	ALT - Alternate Route
(220)	Wye - Wye Route connector

P - Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.

The VDOT Maintainenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

#### Virginia Department of Transportation Traffic Engineering Division 2018

#### Annual Average Daily Traffic Volume Estimates By Section of Route Town of Painter

Route	Jurisdiction	Langth AADT	T 04	4Tiro	Due		Truck		QC	K	QK	Dir	AAWDT		
noute	Junsuiction	Length AAD	T QA	4Tire	bus	2Axle	3+Axle	1Trail	2Trail	QC	Factor	QN	Factor	AAWDI	QVV
	From:	SCL Painter													
13 Lankford Hwy	Town of Painter (Maint: 01)	0.43 1800	0 N	92%	1%	1%	1%	6%	0%	Ν	0.081	F	0.518	16000	Ν
	To:	01-614 Hic	cman St												
	From:	01-614 Wayside Dr													
13 Lankford Hwy	Town of Painter (Maint: 01)	0.46 <b>180</b> 0	0 G	92%	1%	1%	1%	6%	0%	F	0.079	F	0.530	16000	G
	To:	NCL Pa	inter												
	From:	US 13 Lankford Hwy													
(182)Mappsburg Rd	Town of Painter (Maint: 01)	0.65 <b>100</b>	) G	97%	0%	1%	0%	1%	0%	С	0.118	F	0.65	1000	G
	То:	ECL Pa	nter												

5/8/2019 7

## Virginia Department of Transportation Traffic Engineering Division 2018 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Painter

				TOWIT OF FAIRLET				
Route	Length	AADT	QA	4Tire Bus 2Axle 3+Axle 1Trail 2Trail QC	K Factor Q	Dir K Factor	AAWDT	QW Year
Town of Painter			_					
Mannahura Pd	0.54	110	`	SCL Painter	NA		NA	10/03/2017
608 Mappsburg Rd	0.54	110 T	. IN	SR 182 Edmund St			INA	10/03/2017
		Fron	n:	WCL Painter	1			
614 Wayside Dr	0.24	920	N	WCL Fainter	NA		NA	06/03/2014
(614) Wayoldo Bi	0.2 1	T-	0:	01-619 Hickman St; 01-1204 Cosby St	Τ΄		107	00/00/2011
$\sim$		Fron	n:	01-619 Wayside Dr; 01-1204 Cosby St				
614 Hickman St	0.02	1900	R		NA		NA	11/21/2017
		10	00	US 13 Lankford Hwy				
O History and Ch	0.00	Fron		01-614; 01-1204 Cosby St			NIA	10/00/0017
619 Hickman St	0.62	440	R	01-620 NCL Painter	NA		NA	10/03/2017
		Fron						
620 Front St	0.14	460	N	WCL Painter	 NA		NA	10/03/2017
(620) 1 TOTA OT	0.14	<b>400</b>		01-619 Boggs Rd; Hickman St; NCL Painter	¬```		14/1	10/00/2017
		Fron	n:	01-1203 Main St				
(1201) Grant St	0.24	150	R	01*1203 Main St	NA		NA	07/27/2017
(1201) Grant St		T	00	01-1206 Savage St				
		Fron	n:	01-1203 Main St				
(1202) Alexine St	0.29	80	R		NA		NA	07/27/2017
01		Te	0:	ECL Painter				
		Fron	n:	01-608 Mappsburg Rd				
1203 Main St	0.08	340	R		NA		NA	07/27/2017
		T		01-1202 Alexine St				
1203 Main St	0.05	460	R		NA		NA	07/27/2017
UI		Т.		01-1207 Callahan Dr				
1203 Main St	0.15	470 From	R	33 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	NA		NA	07/27/2017
017		To	2	01-1201 Grant St				
(1203) Main St	0.05	440	R	01-1201 Grant St	NA		NA	07/27/2017
1200		Te	00	SR 182 Mappsburg Rd				
		Fron	n:	WCL Painter				
(1204) Cosby St	0.31	840	N		NA		NA	07/27/2017
01		T	00	01-614; 01-619				
_		Fron	n:	01-619 Hickman St				
1205 Duer St	0.09	930	R		NA		NA	07/27/2017
		T	00	US 13 Lankford Hwy				
$\sim$		Fron		0.10 MW 01-1201, End State Maintenance				
(1206) Savage St	0.20	180	R		NA		NA	07/27/2017
		Te		0.10 ME 01-1201, End State Maintenance				
0.11.1.00		From		01-1203 Main St	ᆜ			0= (0= (00 , 1=
(1207) Callahan St	0.06	70	R		NA		NA	07/27/2017
		Fron		SR 182 Mappsburg Rd				
(1207) Callahan Dr	0.12	40	R		NA		NA	07/27/2017
		Т		01-1210 Callahan Dr				
<u> </u>		From		SR 182 Mappsburg Rd	<b>_</b>			
(1208) Railroad Ave	0.10	120	R	01 1200 Pl 94	NA T		NA	07/27/2017
				01-1209 Fleming St				
Classics Ct	0.00	Pron		01-1208 Railroad Ave			NIA	07/07/004
1209 Fleming St	0.09	<b>20</b>	R	01 1201 Crost St	NA		NA	07/27/2017
		Fron		01-1201 Grant St	1			
Callahan Dr	0.05		"L	01-1202 Alexine St	 NA		NA	07/27/2017
(1210) Callahan Dr	0.03	<b>30</b>		01-1207 Callahan Dr			14/4	01/21/2017
			1	or 1207 Cananan Di				

5/8/2019 8