

2020
Virginia Department of Transportation
Daily Traffic Volume Estimates
Including Vehicle Classification Estimates
where available

Special Locality Report
148
Town of Richlands

Information in this report is included in Report
92
(Tazewell County)

Prepared By
Virginia Department of Transportation
Traffic Engineering Division

In Cooperation With
U.S. Department of Transportation
Federal Highway Administration

The reported 2020 AADTs represent the best estimate of 2020 average daily traffic, however, this year's AADTs do vary from normal traffic in the years prior to 2020 due to COVID-19. The reported AADTs may not represent typical traffic for a given day or period within the year as the drastic seasonal variations were normalized through the factoring process. The 2020 publications are therefore colored to draw users attention to the fact that uses of the 2020 published estimates versus alternative data sources should be determined at users' discretion based on the objectives or nature of the analyses being performed.

The estimated 2020 DVMT for the entire state maintained network total to 208,000,000, which has trended down by 11 percent compared to the 2019 level of 234,000,000. For most traffic links across the state, the estimated 2020 AADTs are also seen to have decreased from their 2019 levels.

Virginia Department of Transportation
Traffic Engineering Division
Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a “Combined Traffic Estimates for Parallel Roadways on this Route” or “Combined Traffic” identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate “NA” for not available.

VDOT’s traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating “NA” for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate “NA” for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of buses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems



Interstate Route

Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.



US Route



Virginia State Route



Frontage Road (F precedes frontage route number)



Secondary Route

Special Routes



Bus - Business Route
Bypass - Bypass Route



Truck - Truck Route
ALT - Alternate Route
Wve - Wve Route connector



P - Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.



The VDOT Maintenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation
 Traffic Engineering Division
 2020
 Annual Average Daily Traffic Volume Estimates By Section of Route
 Town of Richlands

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW
							2Axle	3+Axle	1Trail	2Trail						
	From: WCL Richland															
67	Town of Richlands	0.20	3800	N	92%	0%	0%	4%	4%	0%	N	0.093	F	0.533	4100	N
	To: Bus US 460 Front St															
	From: US 460 Raven															
67 460	Town of Richlands (Maint: 92)	1.38	11000	G	96%	0%	1%	1%	2%	0%	F	0.085	F	0.534	12000	G
	To: CL Richlands															
	From: US 460; BUS US 460															
67 460	Front St	Town of Richlands	0.27	10000	G	97%	0%	1%	1%	0%	C	0.088	F	0.516	11000	G
	To: BUS US 460 P, 2nd St															
	From: BUS US 460 P, 2nd St															
67 460	Front St	Town of Richlands	0.58	4200	G	97%	0%	1%	1%	0%	F	0.094	F	0.549	4500	G
	Combined Traffic Estimates for 2 Parallel Roadways on this Route:		0.94	9400	G	97%	1%	1%	0%	0%	F	0.089	F	0.777	10000	G
	To: SR 67 P Railroad Ave															
	From: SR 67 P Railroad Ave															
67 460 460	Front St	Town of Richlands	0.04	3600	F	99%	0%	1%	0%	0%	F	0.092	F		3900	F
	Combined Traffic Estimates for 2 Parallel Roadways on this Route:		0.08	6400	N	96%	0%	1%	1%	0%	N	NA			6800	N
	To: BUS US 460 Front St															
	From: BUS US 460 Front St															
67	Norfolk St	Town of Richlands	0.04	660	F	97%	0%	2%	0%	0%	C	0.112	F	0.642	700	F
	Combined Traffic Estimates for 2 Parallel Roadways on this Route:		0.08	1200	F	97%	0%	2%	1%	0%	F	0.109	F	0.891	1200	F
	To: 2nd St															
	From: Norfolk St															
67 460	2nd St	Town of Richlands	0.05	2800	N	93%	0%	1%	2%	3%	N	0.097	F	0.682	3000	N
	Combined Traffic Estimates for 2 Parallel Roadways on this Route:		0.10	6400	N	96%	0%	1%	1%	1%	N	NA			6800	N
	To: SR 67 Par, Bus US 460 Par Railroad St															
	From: SR 67 Par, Bus US 460 Par; 2nd St															
67	Railroad St	Town of Richlands	0.41	2800	F	93%	0%	1%	2%	3%	F	0.097	F	0.682	3000	F
	To: US 460															
	From: US 460															
67	Railroad St	Town of Richlands	0.92	1500	F	96%	0%	1%	2%	0%	C	0.096	F	0.528	1600	F
	To: NCL Richlands															
	From: Bus US 460 Front St															
67	Railroad St	Town of Richlands	0.05	500	F	96%	0%	1%	2%	0%	F	0.12	F		520	F
	Combined Traffic Estimates for 2 Parallel Roadways on this Route:		0.10	1200	F	97%	0%	2%	1%	0%	F	0.109	F	0.890	1200	F
	To: SR 67 Second St															
	From: WCL Richlands															
460	Town of Richlands (Maint: 92)	0.18	6600	N	96%	0%	1%	1%	2%	0%	N	0.081	F	0.523	7300	N
	To: SR 67															
	From: SR 67															
460 67	Town of Richlands (Maint: 92)	1.38	11000	G	96%	0%	1%	1%	2%	0%	F	0.085	F	0.534	12000	G
	To: Bus US 460															
	From: Bus US 460															
460	Town of Richlands (Maint: 92)	1.32	8900	G	96%	0%	1%	1%	2%	0%	F	0.083	F	0.503	9800	G
	To: SR 67															
	From: SR 67															
460	Town of Richlands (Maint: 92)	0.38	11000	F	96%	0%	1%	1%	2%	0%	C	0.101	B	0.536	12000	F
	To: ECL Richlands															

Virginia Department of Transportation
 Traffic Engineering Division
 2020
 Annual Average Daily Traffic Volume Estimates By Section of Route
 Town of Richlands

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW
							2Axle	3+Axle	1Trail	2Trail						
Bus 460 67 Front St	From: [] Town of Richlands	0.27	10000	G	97%	0%	1%	1%	1%	0%	C	0.088	F	0.516	11000	G
	To: [] From: []	Bus US 460 P, 2nd St														
Bus 460 67 Front St	Town of Richlands	0.58	4200	G	97%	0%	1%	1%	1%	0%	F	0.094	F	0.549	4500	G
		Combined Traffic Estimates for 2 Parallel Roadways on this Route:		9400	G	97%	1%	1%	0%	1%	F	0.089	F	0.777	10000	G
	To: [] From: []	SR 67 P Railroad Ave														
Bus 460 67 Front St	Town of Richlands	0.04	3600	F	99%	0%	1%	0%	0%	0%	F	0.092	F		3900	F
		Combined Traffic Estimates for 2 Parallel Roadways on this Route:		6400	N	96%	0%	1%	1%	0%	N	NA			6800	N
	To: [] From: []	SR 67 Norfolk St														
Bus 460 Front St	Town of Richlands	0.18	2600	F	99%	0%	1%	0%	0%	0%	F	0.092	F		2700	F
		Combined Traffic Estimates for 2 Parallel Roadways on this Route:		5200	G	98%	1%	1%	0%	0%	F	0.093	F		5500	G
	To: [] From: []	Bus US 460 P 2nd St														
Bus 460 Front St	Town of Richlands	0.92	5100	F	99%	0%	1%	0%	0%	0%	C	0.106	F	0.557	5400	F
	To: [] From: []	WCL Cedar Bluff														
Bus 460 67 2nd St	From: [] Town of Richlands (Maint: 92)	0.57	5200	G	97%	1%	1%	0%	0%	0%	F	0.096	F		5500	G
		Combined Traffic Estimates for 2 Parallel Roadways on this Route:		9400	G	97%	1%	1%	0%	1%	F	0.089	F	0.777	10000	G
	To: [] From: []	SR 67 Railroad Ave														
Bus 460 67 67 2nd St	Town of Richlands	0.05	2800	N	93%	0%	1%	2%	3%	0%	N	0.097	F	0.682	3000	N
		Combined Traffic Estimates for 2 Parallel Roadways on this Route:		6400	N	96%	0%	1%	1%	0%	N	NA			6800	N
	To: [] From: []	SR 67 Norfolk St														
Bus 460 2nd St	Town of Richlands (Maint: 92)	0.25	2600	G	97%	1%	1%	0%	0%	0%	C	0.105	F		2700	G
		Combined Traffic Estimates for 2 Parallel Roadways on this Route:		5200	G	98%	1%	1%	0%	0%	F	0.093	F		5500	G
	To: [] From: []	Bus US 460 Front St														

Virginia Department of Transportation
Traffic Engineering Division
2020
Annual Average Daily Traffic Volume Estimates By Section of Route
Town of Richlands

Route	Length	AADT	QA	4Tire	Bus	-----Truck----- 2Axle 3+Axle 1Trail 2Trail	QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
Town of Richlands													
5	Rec. Park Rd	0.59	570	G		From: Dead End To: SCL Richlands		0.303	F	0.572	570	G	2020
6	Purcell Rd	0.25	80	G		From: Dead End To: 148-4 Birmingham Rd		0.184	F	0.556	80	G	2020
6	Purcell Rd	0.65	500	G		From: 148-4 Birmingham Rd To: SCL Richlands		0.108	F	0.638	500	G	2020
7	Burnett St	0.36	760	G		From: Dead End To: WCL Richlands		0.085	F	0.525	760	G	2020
8	Sandy Lane	0.18	80	G		From: Cul-de-Sac To: 148-13 Cresswood Dr		0.142	F	0.563	80	G	2020
8	Cresswood Dr	0.07	190	G		From: 148-13 Cresswood Dr To: 148-12 Valley Dr		0.134	F	0.559	190	G	2020
8	Cresswood Dr	0.21	300	G		From: 148-12 Valley Dr To: 148-11 Plantation Dr		0.116	F	0.558	300	G	2020
8	Cresswood Dr	0.16	490	G		From: 148-11 Plantation Dr To: 148-9 Fairmont Dr		0.120	F	0.536	490	G	2020
8	Cresswood Dr	0.17	710	G		From: 148-9 Fairmont Dr To: 148-15 Terry Dr		0.111	F	0.503	710	G	2020
8	Cresswood Dr	0.27	1300	G		From: 148-15 Terry Dr To: 148-4700 Kents Ridge Rd		0.112	F	0.794	1300	G	2020
9	Fairmont Dr	0.07	210	G		From: 148-10 Linwood Dr To: 148-8 Cresswood Dr		0.129	F	0.546	210	G	2020
10	Linwood Dr	0.20	140	G		From: 148-9 Fairmont Dr To: 148-11 Plantation Dr		0.124	F	0.619	140	G	2020
10	Linwood Dr	0.08	40	G		From: 148-11 Plantation Dr To: Cul-de-Sac		0.147	F	0.75	40	G	2020
11	Plantation Dr	0.07	200	G		From: Cul-de-Sac To: 148-15 Terry Dr		0.131	F	0.612	200	G	2020
11	Plantation Dr	0.27	70	G		From: 148-15 Terry Dr To: 148-13 Cresswood Dr		0.158	F	0.6	70	G	2020
11	Plantation Dr	0.06	40	G		From: 148-13 Cresswood Dr To: 148-8 Cresswood Dr		0.173	F	0.737	40	G	2020
12	Valley Dr	0.16	40	G		From: 148-8 Cresswood Dr To: 148-10 Linwood Dr		0.217	F	0.571	40	G	2020
13	Cresswood Dr	0.14	140	G		From: 148-10 Linwood Dr To: 148-14 Cresswood Dr		0.148	F	0.8	140	G	2020
13	Cresswood Dr	0.08	60	G		From: 148-14 Cresswood Dr To: 148-14 Valley Dr		0.154	F	0.727	60	G	2020
13	Cresswood Dr	0.16	70	G		From: 148-14 Valley Dr To: 148-15 Hawthorn Ln		0.149	F	0.667	70	G	2020
14	Valley Dr		40	G		From: 148-15 Hawthorn Ln To: 148-8 Cresswood Dr; Sandy Lane		0.217	F	0.571	40	G	2020
15	Terry Dr	0.27	70	G		From: 148-13 Cresswood Dr To: 148-12 Valley Dr		0.176	F	0.615	70	G	2020
						From: 148-13 Hawthorne La To: 148-11 Plantation Dr							

Virginia Department of Transportation
Traffic Engineering Division
2020
Annual Average Daily Traffic Volume Estimates By Section of Route
Town of Richlands

Route	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
						2Axle	3+Axle	1Trail	2Trail							
Town of Richlands																
(15) Terry Dr	0.38	350	G								0.133	F	0.741	350	G	2020
(15) Terry Dr	0.07	600	G								0.141	F	0.721	600	G	2020
(16) Gary Dr	0.39	110	G								0.146	F	0.639	110	G	2020
(17) Oxford St		340	F								0.114	F	0.519	340	F	2020
(18) Hunter Ridge Rd	0.51	110	G								0.15	F	0.524	110	G	2020
(19) Daw Rd	0.73	350	F								0.123	F	0.651	350	F	2020
(20) Laramie Rd		370	G								0.126	F	0.598	370	G	2020
(21) Birmingham Rd	1.22	90	G								0.12	F	0.52	90	G	2020
(4700) Kents Ridge Rd	0.46	2400	F	98%	0%	1%	0%	0%	0%	C	0.096	F	0.508	2600	F	2020
(4700) Kents Ridge Rd	0.34	2500	F	98%	0%	1%	0%	0%	0%	C	0.095	F	0.517	2700	F	2020
(4700) Kents Ridge Rd	0.62	3300	F	98%	0%	1%	0%	0%	0%	C	0.095	F	0.562	3500	F	2020
(4700) Kent Ridge Rd	0.29	4100	G	98%	0%	1%	0%	0%	0%	F	0.091	F	0.601	4400	G	2020
(4700) Kent Ridge Rd	0.47	4200	F	98%	0%	1%	0%	0%	0%	F	0.094	F	0.561	4500	F	2020
S Front St		300	F								0.136	F	0.584	310	F	2020
Veteran Dr		1400	F								0.109	F	0.681	1400	F	2020