2020

Virginia Department of Transportation Daily Traffic Volume Estimates Including Vehicle Classification Estimates

where available

Special Locality Report 216

Town of Elkton

Information in this report is included in Report

82

(Rockingham County)

Prepared By

Virginia Department of Transportation Traffic Engineering Division

In Cooperation With

U.S. Department of Transportation Federal Highway Administration

The reported 2020 AADTs represent the best estimate of 2020 average daily traffic, however, this year's AADTs do vary from normal traffic in the years prior to 2020 due to COVID-19. The reported AADTs may not represent typical traffic for a given day or period within the year as the drastic seasonal variations were normalized through the factoring process. The 2020 publications are therefore colored to draw users attention to the fact that uses of the 2020 published estimates versus alternative data sources should be determined at users' discretion based on the objectives or nature of the analyses being performed.

The estimated 2020 DVMT for the entire state maintained network total to 208,000,000, which has trended down by 11 percent compared to the 2019 level of 234,000,000. For most traffic links across the state, the estimated 2020 AADTs are also seen to have decreased from their 2019 levels.

Virginia Department of Transportation Traffic Engineering Division Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of buses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems

North
81 Interstate Route
Interstate Route

Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.

29 US Route

7 Virginia State Route

F241) Frontage Road (F precedes frontage route number)

(600) Secondary Route

Special Routes

Bus Bus - Business Route
Bypas - Bypass Route
Truck - Truck Route
ALT ALT - Alternate Route
Wye - Wye Route connector

P - Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.

The VDOT Maintainenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation Traffic Engineering Division 2020 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Elkton

Route	Jurisdiction	Length AADT C	A 4T	ire B	-		Truc	ck		QC	K	QK	Dir Factor	AAWDT	QW
		Longin AADI C			2	2Axle 3	3+Axle	1Trail	2Trail	<u> </u>	Factor	S.I.			
~~	From:	WCL Elkton													
(33) Spotswood Trail	Town of Elkton (Maint: 82)	0.69 9300	N 93	3% 1	%	1%	1%	4%	0%	Ν	0.092	F	0.688	9300	N
\rightarrow	To:	ECL Elkton													
Bus	From:	WCL Elkton; River I	Rd												
33 Spottswood Ave	Town of Elkton (Maint: 82)	0.37 6500	G 99	9% 0	%	1%	0%	0%	0%	С	0.089	F	0.617	6500	G
	To	Spottswood Terr													
Bus	From:	•			_,		0.01			_		_			_
(33) Spottswood Ave	Town of Elkton (Maint: 82)		G 99	9% 0	%	1%	0%	0%	0%	F	0.096	F	0.509	2500	G
	10:	Stuart Ave													
~~~	From:	SCL Elkton													
340 S Stuart Ave	Town of Elkton (Maint: 82)	5400	N 93	3% 1	%	1%	1%	4%	0%	Ν	0.093	F	0.549	5300	N
	To	US 33				_									
Bus	Town of Elliton (Moints 00)			20/ 1	0/	10/	10/	40/	00/	N.I	0.000	F	0.540	F000	N.
340 33 S Stuart Ave	Town of Elkton (Maint: 82)	5400	N 93	3% 1	%	1%	1%	4%	0%	N	0.093	Г	0.549	5300	N
~~~	To: From	Bus US 33													
(340)N Stuart Ave	Town of Elkton (Maint: 82)	0.19 7400	N 97	7% 1	%	1%	0%	2%	0%	Ν	0.089	F	0.615	7400	Ν
	To	Spottswood Ave				٦									
340 N Stuart Ave	Town of Elkton (Maint: 82)	•	G 97	7% 1	%	1%	0%	2%	0%	С	0.089	F	0.615	7400	G
340	To:	NCL Elkton, 82-1706 Shenar	-		•					_					

6/13/2021

Virginia Department of Transportation Traffic Engineering Division 2020 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Elkton

Route	Length	AADT	QA	4Tire	Bus		Tru 3+Axle			QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
own of Elkton		From									- i					
8 Quail Run Dr	0.15	520	G			Ві	us US 33				0.127	F	0.515	520	G	2020
8 Quail Run Dr	0.08	150 From	H G				rning Dove				0.151	F	0.592	150	G	2020
9 Morning Dove Lane	0.05	From	G				hickadee C	licie			0.122	F	0.571	300	G	2020
g)g 2010 24.10		To				216-8	Quail Run	Dr				•				
10) Chickadee Circle	0.05	60 To	G				ıl-de-Sac				0.152	F	0.546	60	G	2020
		From	:				Quail Run l L Elkton)r								
11) W Washington Ave	0.05	960	G					Y			0.093	F	0.583	960	G	2020
E Washington Ave	0.20	460 From	G				East Side F	·			0.125	F	0.628	460	G	2020
E Washington Ave	0.03	270 From	G				·16 High St				0.196	F	0.729	270	G	2020
E Washington Ave	0.09	110 To	G				-14 High St -12 Pine St				0.217	F	0.842	110	G	2020
		From	:		2		Washingto									
Pine St	0.07	47	G								0.171	F	0.684	47	G	2020
Pine St	0.05	10	G				5 Spring Avead End	re			0.512	F	0.571	10	G	2020
Summit Ave	0.25	730 From	G	99%	1%		East Side I	Iwy 0%	0%	С	0.104	F	0.652	330	G	2020
9		To From	<u>.</u>				-14 High St									
Summit Ave	0.38	210 To	G	99%	0%	0% US 33 S	0% potswood 1	0% Γrail	0%	С	0.146	F	0.629	210	G	2020
14) High St	0.08	160	G			216-17	Prospect A	ve			0.104	F	0.525	160	G	2020
14) High St	0.09	130 From	G				Summit A				0.138	F	0.756	130	G	2020
		From			2		Washingto ead End	n Ave								
Spring Ave	0.14	40	G								0.207	F	0.588	40	G	2020
15) Spring Ave	0.12	40 From	G		21		shall Ave;				0.215	F	0.529	40	G	2020
		To					-12 Pine St									
High St	0.06	120	G		2		Washingto				0.127	F	0.529	120	G	2020
16) Marshall Ave	0.09	48 From	G				5 Spring Av	/e			0.142	F	0.667	48	G	2020
		To	c				ead End 14 High St									
Prospect Ave	0.10	110	G				ead End				0.130	F	0.531	110	G	2020
		From					CL Elkton									
Blue And Gold Dr	0.31	850	G			8	32-9750				0.250	F	0.7	850	G	2020
		Fron				Ві	us US 33									
W. Spotswood Ave	0.29	2900 To	G	98%	1%	1% St	0% uart Ave	0%	0%	С	0.095	F	0.699	2900	G	2020

Virginia Department of Transportation Traffic Engineering Division 2020 Annual Average Daily Traffic Villeton Estimates By Section of Route

Town	of Elktor

Route	Length	AADT	QA	4Tire	Bus		Tru			QC	K	QK	Dir	AAWDT	QW	Year
Town of Elkton						2Axie	3+Axle	1 I rail	21rail		Factor		Factor			
Town of Elkton		From				Str	art Ave									
(1924) E. Spotswood Ave	0.51	2700	G	98%	1%	1%	0%	0%	0%	F	0.096	F	0.666	2700	G	2020
		To From				N	orth St									
Newtown Rd	0.41	2200	G	98%	0%	1%	1%	0%	0%	С	0.096	F	0.613	2200	G	2020
		To From				82-891 N	It Paran Cl	n Rd								
(1924) Newtown Rd	0.39	1600	N	98%	0%	0%	1%	0%	0%	Ν	0.096	F	0.646	1600	Ν	2020
		To				EC	L Elkton									
		From				Spott	swood Ave									
(1925) North St	0.65	2200	G	98%	0%	0%	1%	0%	0%	С	0.094	F	0.574	2200	G	2020
		To				82-623	; ECL Elkt	on								
		From		C Street												
Ashby Ave		120	G								0.267	F	0.578	120	G	2020
		To				В	Street									

6/13/2021