2020

Virginia Department of Transportation Daily Traffic Volume Estimates Including Vehicle Classification Estimates

where available

Special Locality Report 253

Town of Leesburg

Information in this report is included in Report

53

(Loudoun County)

Prepared By

Virginia Department of Transportation Traffic Engineering Division

In Cooperation With

U.S. Department of Transportation Federal Highway Administration

The reported 2020 AADTs represent the best estimate of 2020 average daily traffic, however, this year's AADTs do vary from normal traffic in the years prior to 2020 due to COVID-19. The reported AADTs may not represent typical traffic for a given day or period within the year as the drastic seasonal variations were normalized through the factoring process. The 2020 publications are therefore colored to draw users attention to the fact that uses of the 2020 published estimates versus alternative data sources should be determined at users' discretion based on the objectives or nature of the analyses being performed.

The estimated 2020 DVMT for the entire state maintained network total to 208,000,000, which has trended down by 11 percent compared to the 2019 level of 234,000,000. For most traffic links across the state, the estimated 2020 AADTs are also seen to have decreased from their 2019 levels.

Virginia Department of Transportation Traffic Engineering Division Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of buses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems

North 81	nterstate Route	Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.
----------	-----------------	----------------------------------------------------------------------------------------------------------------------------

29 US Route

7 Virginia State Route

Frontage Road (F precedes frontage route number)

(600) Secondary Route

Special Routes

Bus Bus - Business Route
Bypas - Bypass Route
Truck - Truck Route
ALT Alternate Route
Wye - Wye Route connector

P - Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.

The VDOT Maintainenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation Traffic Engineering Division 2020

Annual Average Daily Traffic Volume Estimates By Section of Route Town of Leesburg

		TOWN OF LCCSDO	urg					1 .			1/		D:		
Route	Jurisdiction	Length AADT	QA 4	1Tire	Bus					QC		QK		AAWDT	QW
	From:	Pug CD 7: WCL Loo	chura			ZAXIE	3+Axie	Hraii	ZTrali		Factor		Factor		
7 Market St West	Town of Leesburg (Maint: 53)			97%	0%	1%	1%	1%	0%	F	0.083	F	0 744	55000	F
/ Market St West	Town or Ecopoling (Maint. 60)			01 70	0 70		1 /0	1 /0	0 70	•	0.000	•	0.7	00000	•
- Leachurg Dunger	Town of Leadurg		F 0	060/	10/	10/	10/	10/	00/	г	0.000		0.705	69000	F
7 (15) Leesburg Bypass	Town of Leesburg	0.44 65000	Γξ	90%	170	170	170	170	0%	Г	0.062	Г	0.725	69000	Г
¬~	Ta: From:	SR 267					101								
7 (15) Leesburg Bypass		43000	G 9	96%	1%	1%	1%	1%	0%	С	0.079	F	0.538	NA	
	To- From	US 15, BUS SR 7 Ma	rket St												
7) Market St East	Town of Leesburg (Maint: 53)	55000		97%	0%	1%	1%	1%	0%	F	0.072	F	0.551	59000	G
	To:	ECL Leesburg													
Bus	From:	WCL Leesburg													
7) Market St	Town of Leesburg	0.02 11000	F 9	99%	0%	0%	0%	0%	0%	F	0.105	F	0.779	12000	F
2	Toe From:	Fairview St													
Bus 7 Market St	Town of Leesburg	0.25 8700	F	99%	0%	0%	0%	0%	0%	C	0 101	F	0.750	9200	F
/ Market of	Town of Eccapuig			JJ 70	0 70	0 70	0 70	0 70	0 70	O	0.101	·	0.750	3200	i
Bus	From:	253-4206 Loudoun	ı St												
7 Market St	Town of Leesburg	0.27 6100	F 9	99%	0%	0%	0%	0%	0%	F	0.106	F	0.801	6400	F
\smile	To	253-4205 Ayr S	t												
Bus 7 Market St	Town of Leesburg			200/	00/	00/	00/	00/	00/	_	0.001	_	0.600	7100	F
7) Market St	Town of Leesburg	0.36 6800	F 8	99%	0%	0%	0%	0%	0%	Г	0.091	Г	0.003	7100	Г
Bus	To: From:	Bus US 15													
7 Market St	Town of Leesburg	0.09 7100	G 9	98%	0%	1%	0%	0%	0%	F	0.075	F	0.506	7600	G
	To	Church St													
Bus	From:			200/	00/	40/	00/	00/	00/	_	0.005	_	0.007	7000	_
7) Market St	Town of Leesburg	0.23 7300	F S	98%	0%	1%	0%	0%	0%	C	0.085	F	0.607	7800	F
Bus	To: From:	253-4206 Loudoun	n St												
7 Market St	Town of Leesburg	0.27 15000	F 9	98%	0%	1%	0%	0%	0%	F	0.088	F	0.517	16000	F
	To														
Bus	From:														
7) Market St	Town of Leesburg	0.71 26000	G 9	98%	0%	1%	0%	0%	0%	F	0.08	F	0.585	NA	
\smile	To:	US 15; SR 7													
~~	From:	SCL Leesburg													
King St	Town of Leesburg	1.09 11000	G 9	95%	1%	1%	1%	2%	0%	С	0.091	F	0.686	11000	G
~	Toe From:	253-4209 Evergreen M	Mill Rd												
15 King St	Town of Leesburg	0.22 23000	F 9	95%	1%	1%	1%	2%	0%	F	0.089	F	0.537	24000	F
~	To:	Bus US 15; Leesburg l													
	From:	Bus US 15 King S		060/	10/	10/	10/	10/	00/	г	0.000	_	0.705	60000	_
15 7 Leesburg Bypass	Town of Leesburg	0.44 65000	2Axle 3+Axle 11rail 21rail Factor Factor 7; WCL Leesburg 8; WC Leesburg Bypass 8	69000	F										
~~~	To- From:	SR 267 Dulles Green													
15) (7) Leesburg Bypass	Town of Leesburg (Maint: 53)			96%	1%	1%	1%	1%	0%	С	0.079	F	0.538	NA	
~ ~	To:	SR 7 Market Street	East												

#### Virginia Department of Transportation Traffic Engineering Division 2020

#### Annual Average Daily Traffic Volume Estimates By Section of Route Town of Leesburg

Route	lurisdiction	Length	AADT	ΟΛ	/Tiro	Ruc		Tru	ck		00	K	OK	Dir	AAWDT	ΟW
rioute	Junsuiction	Length	AADI	Q,	41116	Dus	2Axle	3+Axle	1Trail	2Trail	QU	Factor	QIV	Factor	AAWDI	QVV
~~ · · -	From:															
(15) Leesburg Bypass	Town of Leesbur	ırg	41000	F	95%	1%	1%	1%	3%	0%	F	0.085	F	0.565	42000	F
~	To: From:	253-4208	Edwards F	erry Rd												
(15) Leesburg Bypass	Town of Leesbur	<u> </u>		F	95%	1%	1%	1%	3%	0%	F	0.080	F	0.557	24000	F
<u> </u>	To:	No	CL Leesburg	3												
Bus	From															
(15) King St	Town of Leesbur	org 0.56	23000	F	96%	3%	0%	0%	0%	0%	F	0.090	F	0.509	24000	F
Bus	To: From:	253-420	00 Catoctin	Circle												
15 King St	Town of Leesbur	o.08	9400	F	96%	3%	0%	0%	0%	0%	F	0.097	F	0.521	9900	F
	Too		Egirfoy St													
Bus	From:												_			
(15) King St	Town of Leesbur	irg 0.40	5400	F	96%	3%	0%	0%	0%	0%	F	0.106	F	0.502	5800	F
Bus	To: From:	253-4	206 Loudou	n St												
(15) King St	Town of Leesbur	irg 0.23	6800	F	98%	0%	1%	0%	0%	0%	С	0.09	F	0.585	7200	F
	Too		North St													
Bus	From:				000/	00/	40/	00/	00/	00/	_	0.407	_	0.500	7400	_
(15) King St	Town of Leesbur	<u> </u>		•	98%	0%	1%	0%	0%	0%	F	0.107	F	0.592	7100	F
			•													
East (267) Dulles Greenway				-	000/	00/	Nº/	00/	∩0/	00/	_	0.175	_		13000	G
267 Dulles Greenway	<b>3</b> \	,		-							' -			0.061	26000	G
	To:	· · · · · · · · · · · · · · · · · · ·			3076	076	170	U 70	170	U 76	Г	0.100	Г	0.001	20000	G
West	Surphysical Column   Length   AADT   QA   4Tire   Bus   2Axle   3+Axle   1Trail   2Trail   QC   Factor   QK   Factor   SR7 Market Street East   Surphysical Column   SR7 Market Street East   SR7 Market St															
West (267) Dulles Greenway	Town of Leesburg (Ma			-	98%	0%	1%	0%	1%	0%	F	0.161	F		13000	G
201) Builds Grooming	• · · · · · · · · · · · · · · · · · · ·	<i>'</i>									F		•	0.861	26000	G
	To:				30 /0	0 /0		0 /0	1 /0	0 /0		3.100		3.001	20000	G

6/13/2021

## Virginia Department of Transportation Traffic Engineering Division 2020 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Leesburg

						10001101	Leesbu	ı g								
Route	Length	AADT	QA	4Tire	Bus		Truc 3+Axle			QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
own of Leesburg		From:				WCL	Leesburg									
Phillips Court	0.06	40	R								NA			NA		12/11/201
		To:					ad End									
F929) Childrens Center Rd	0.25	330	R			Cul-	-de-Sac				NA			NA		11/12/201
F929 Official office file	0.23	To:				End State	Maintenan	ice						IVA		11/12/201
_		From:				253-4200 C	Catoctin Ci	rcle								
9282 53	0.08	160	R								NA			NA		12/09/201
		To:					ad End									
0284)		660	R		1	Douglas Ele	mentary Sc	chool			NA			NA		02/18/20
9284		To:			I	Douglas Ele	mentary Sc	chool								
		From				Dea	ad End									
9536 Loudoun Co High Sch	ool 0.13	1100	R								NA			NA		12/09/201
		From:					Dry Mill F									
1 Battlefield Pkwy	0.83	7900	F	98%	1%	Bus US 1%	15 King St 0%	t 0%	0%	С	0.114	F	0.546	8300	F	2020
.,		To			,-		esburg Bypa		- / -							
1 Battlefield Pkwy	0.42	8200	F	98%	1%	0%	о% (25 от 19 от 1	0%	0%	С	0.126	F	0.732	8700	F	2020
		Tor				Smar	rtts Lane									
1 Battlefield Pkwy	0.98	8600	F	98%	1%	0%	0%	0%	0%	С	0.122	F	0.737	9100	F	2020
		To: From:					ls Ferry Rd Evans Rd									
1 Battlefield Pkwy	0.59	14000	F	98%	1%	0%	0%	0%	0%	С	0.093	F	0.514	14000	F	2020
		To:				SR 7 M	Iarket St E									
$\widehat{}$		From:					esburg Bypa									
3 Fort Evans Rd	0.83	11000	F	98%	1%	1%	0%	0%	0%	С	0.1	F	0.518	12000	F	2020
		From:			ECL Le	esburg; 53-	7 Market S		KWY							
4 Plaza St	0.44	9600	F	95%	3%	1%	1%	0%	0%	F	0.095	F	0.553	10000	F	2020
		To:			2	53-4208 Ed	lwards Ferr	v Rd								
4 Plaza St	0.48	3500	G	95%	3%	1%	1%	0%	0%	С	0.143	F	0.776	3700	G	2020
		To:				Rı	ust Dr									
Plaza St	0.32	4300	F	95%	3%	1%	0%	0%	0%	С	0.105	F	0.663	4600	F	2020
		To					ield Pkwy									
5 River Creek Pkwy	0.29	19000	F	99%	0%	SR 7 I	Market St 0%	0%	0%	F	0.116	F	0.755	20000	F	2020
5 River Creek Pkwy	0.20	To:		0070	0 70		Leesburg	070	070				0.700	20000		2020
		From:					tlefield Pky	wy								
4200 Catoctin Circle	0.84	2100	F	96%	3%	1%	0%	0%	0%	С	0.113	F	0.595	2300	F	2020
$\sim$		To:				53-4208 Ed					$\supset$					
Catoctin Circle	0.29	6500	F	98%	1%	1%	0%	0%	0%	F	0.108	F	0.535	6900	F	2020
Onto alla Olaska	0.47	From		000/	40/		Market St E		00/	_			0.500	45000		0000
Catoctin Circle	0.17	14000		98%	1%	1%	0%	0%	0%	F	0.091	F	0.502	15000	F	2020
(4200) Catoctin Circle	0.63	14000	F	98%	1%	So 1%	outh St 0%	0%	0%	С	0.093	F	0.510	15000	F	2020
Catoctin Circle	0.00	14000		30 /6	1 /0			0 /6	0 /6		0.033	'	0.510	13000	'	2020
Catoctin Circle	0.57	7400	F	98%	1%	1%	King St S	0%	0%	F	0.114	F	0.574	7800	F	2020
		To					Mill Rd									
4200) Catoctin Circle	0.38	3600 From:	F	98%	1%	1%	0%	0%	0%	F	0.126	F	0.731	3800	F	2020
		To:				Children	s Center R	d								
4200 Catoctin Circle	0.29	3100	F	98%	1%	1%	0%	0%	0%	F	0.117	F	0.705	3300	F	2020
_		To: From:				Marl	ket St W									
Fairview St	0.64	1600	F	97%	2%	1%	0%	0%	0%	С	0.093	F	0.525	1700	F	2020
		To			Ι	Ory Mill Rd	; NCL Lees	sburg								

6/13/2021 10

## Virginia Department of Transportation Traffic Engineering Division 2020 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Leesburg

						TOWIT OF LEES DE	μĠ								
Route	Length	AADT	QA	4Tire	Bus		•		QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
own of Leesburg		From				CCL I 1									
201) Sycolin Rd	1.61	5100	` <u></u>	94%	2%		0%	0%	F	0.111	F	0.666	5400	F	2020
3,201)		To . To		0.70						<u> </u>	•	0.000	0.00	•	
Sycolin Rd	0.64	7900	G	94%	2%			0%	F	0.096	F	0.634	8400	G	2020
201)		То	d .			Bus SR 7									
		From	c			WCL Leesburg									
Dry Mill Rd		2500	F	98%	0%	1% 0%	0%	0%	С	0.102	F	0.566	2600	F	2020
		To	-			Lee Ave									
205) Dry Mill Rd	0.25	2300	F	98%	### ATIVE BUS   2Axle 3+Axle 1Trail 2Trail   QC   Fa   SCL Leesburg		0.106	F	0.586	2400	F	2020			
		From	-			Catoctin Circle				$\neg$					
Dry Mill Rd	0.49	1400	F	98%	0%	1% 0%	0%	0%	С	0.103	F	0.52	1500	F	2020
		To													
Ayr St	0.09	440	T	99%	0%		0%	0%	C	0.166	F		470	F	2020
205) Ayı Ot	0.00	To	•	33 76	0 70		0 70	0 78		0.100			470	<u>I</u>	2020
		From	c												
Loudoun St	0.28	3200	F	99%	0%		0%	0%	С	0.092	F	0.875	3400	F	2020
		To													
Loudoun St	0.35	5000 From	F	98%	0%			0%	F	0.096	F	0.684	5300	F	2020
			-												
206) Loudoun St	0.30	7400	: <u>1</u>	98%	0%		0%	0%	С	0.088	F	0.571	7800	F F F	2020
		То	c				3,0	3,3							
		From	c												
Edwards Ferry Rd	0.11	2100	F	98%	0%		0%	0%	С	0.108	F	0.518	2200	F	2020
		To	-			Harrison St									
Edwards Ferry Rd	0.41	2400 From	F	99%	0%		0%	0%	С	0.109	F	0.563	2500	F	2020
9		To				Prince St									
Edwards Ferry Rd	0.20	5800 From	F	99%	0%		0%	0%	F	0.1	F	0.528	6100	F	2020
,		To													
Edwards Ferry Rd	0.15	6200 From	F	99%	0%		0%	0%	F	0.099	F	0.545	6500	F	2020
208) 20114140 1 011) 114	00	T-0-0									•	0.0.0	0000	•	
Edwards Ferry Rd	0.51	24000	F	99%	0%		0%	0%	F	0.107	F	0.621	25000	F	2020
Edwards Ferry Rd	0.01	<b>2</b> -1000		0070	0 70		0 70	070		0.107	•	0.021	20000	G F F F F F F F F F F F F F F F F F F F	2020
Edwards Ferry Rd	0.66	12000		99%	0%		0%	0%	F	0.104	F	0.533	13000	F	2020
208) Lawards Forty Fla	0.00	To		0070	0 70			070		0.104	•	0.000	10000	•	2020
		From	e e												
Evergreen Mill Rd	1.01	7200	F	96%	0%		1%	0%	С	0.103	F	0.606	7600	F	2020
		To													
Evergreen Mill Rd	0.01	7700	i N	94%	1%		1%	0%	N	0.098	F	0.596	8100	N	2020
		То													
		From	c												
210) Country Club Dr	0.40	2400	F	95%	3%	1% 1%	0%	0%	F	0.100	F	0.701	2600	F	2020
		To				US 15 King St									
		From				Trailview Blvd									
Cardinal Park Dr		7300	F							0.087	F	0.627	7300	F	2020
		То				Market St									
0		From	ь			Grafton Way					_		4=00	_	
Catoctin Circle		1500	F			C 4 . F.				0.116	F	0.652	1500	F	2020
		10	_			Southview Pl									
Gayarnara Dr		From	ь			Country Club Di				0.116	_	0.610	700	Г	2000
Governors Dr		730 _{To}	F			US 15				0.116	F	0.613	730	F 20	2020
		From													
		From				Dead End									
Trailview Blvd Prop		5400	F							0.089	F	0.589	5400	F	2020

6/13/2021